BRIMFIELD FIRE DEPARTMENT

Massachusetts One and Two Family Dwellings					
ALL SMOKE DETECTORS MUST BE CEILING MOUN			7		
	Year built or Substantially Modified				- / - /
	Before 1975	1975 - 8/27/97	8/27/97 - 2007	1/1/08 - 2/4/11	2/4/11 - Present
Smoke Detector Powered by:					
Battery Operated	Allowed	Not Allowed	Not Allowed	Not Allowed	Not Allowed
Hardwired, Interconnected	Allowed	Not Allowed	Not Allowed	Not Allowed	Not Allowed
Hardwired, Interconnected w/ battery backup	Recommended	Required	Required	Required	Required
ype of Smoke Detector					
	Photoelectric with 10 -	Photoelectric OR	Photoelectric OR	Photoelectric and	Photoelectric Ph
Dutside 20 FT. of kitchen or bathroom	year, sealed, non-	Ionization	Ionization	Ionization OR Dual	
	rechargeable, non-			Detector*	
	replaceable replaceable				
	Photoelectric with 10 -				
<u>Vithin 20 FT.</u> of kitchen or bathroom	year, sealed, non-	Photoelectric	Photoelectric	Photoelectric	Photoelectric Ph
	rechargeable, non-				
	replaceable				
Carbon Monoxide Detector Powered by:	MUST BE IN THE HALLY	VAY OUTSIDE THE SL	EEPING AREA,		
	WITHIN 10 FEET OF EAC	CH BEDROOM DOOR	, ON ALL LEVELS OF	THE RESIDENCE	
attery OR Plug in with battery backup	Allowed	Allowed	Allowed	Not Allowed	Not Allowed
Hardwired, interconnected w/ battery backup	Allowed	Allowed	Allowed	Required	Required
ocations that Smoke Detectors are required:					
Basement	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
very Habitable Level	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
ase of all stairs	Smoke	Smoke	Smoke	Smoke	Smoke
On ceiling outside each sleeping area(hallway)	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
nside every bedroom	Not Required	Not Required	Smoke	Smoke	Smoke
inished attic (habitable)	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO	Smoke/CO
Garage(attached)	Not Required	Not Required	Not Required	Heat Detector	Heat Detector

Combination Smoke and Carbon Monoxide alarms MUST have a voice feature

CO Detectors are required in all homes which are heated by fossil fuels or have an attached garage

Smoke Detectors must be replaced 10 years from the date of manufacture per MA Fire Code